



	ProxCARD® II	ISOProx® II	DuoProx® II	Smart ISOProx II™	Smart DuoProx® II	iCLASS® Prox	MIFARE®/Prox	MicroProx®Tag
READ RANGE:								
ProxPoint® Plus	Up to 3.0" (7.5 cm)	Up to 2.5" (6.5 cm)			Up to 2.5" (6.5 cm)		Up to 2.0" (5.0 cm)	
MiniProx®	Up to 5.5" (14.0 cm)	Up to 5.0" (12.5 cm)			Up to 5.0" (12.5 cm)		Up to 2.5" (6.5 cm)	
Thinline® II	Up to 5.5" (14.0 cm)	Up to 5.0" (12.5 cm)			Up to 5.0" (12.5 cm)		Up to 3.0" (7.5 cm)	
ProxPro®	Up to 8.0" (20.5 cm)	Up to 7.0" (18.0 cm)			Up to 7.0" (18.0 cm)		Up to 4.0" (10.0 cm)	
ProxPro® II	Up to 9.0" (23.0 cm)	Up to 8.0" (20.0 cm)			Up to 8.0" (20.0 cm)		Up to 4.5" (11.5 cm)	
MaxiProx®	Up to 29.0" (74.0 cm)	Up to 20.0" (51.0 cm)			Up to 20.0" (51.0 cm)		Up to 15.0" (38.0 cm)	
EntryProx™	Up to 3.0" (7.5 cm)	Up to 2.5" (6.5 cm)			Up to 2.5" (6.5 cm)		Up to 2.0" (5.0 cm)	
Prox80™	Up to 5.5" (14.0 cm)	Up to 5.0" (12.5 cm)	Up to 2.5" (6.0 cm)		Up to 5.0" (12.5 cm)		Up to 2.5" (6.0 cm)	
Memory Size/ Application Area	N/A					2k bits with two application areas; 16k bits with two application areas, 16k bits with 16 application areas; 32k bits (16k/2+16k/1), 32k bits (16k/16+16k/1)	MIFARE 1K: 1K Byte (8k bits) in 16 64-byte Sectors MIFARE 4K: 4K Byte (32k bits) in 40 Sectors: 32 sectors of 64 bytes, 8 sectors of 256 bytes.	N/A
HID Proximity 125 kHz	Yes							
Contact Smart Chip Module Embeddable	No			Yes		Optional		No
Magnetic Stripe	No	Yes	No	Yes		No		
Printable	Yes					Optional		Yes
Standard HID Artwork	Optional							
Slot Punch	Vertical	Horizontal or vertical optional		Vertical optional			No	
Visual Security Options	N/A	Yes						N/A
Additional Security Options	Corporate 1000							